

AUJETDP

系列自动泵系统

SERIES AUTOMATIC DEEP WELL PUMP



AUJETDP series automatic supplying water systems combined with a centrifugal pump, a pressure tank, an airtight pressure switch, a pressure gauge, a nozzle, an ejector, The change of its needing power is smooth while the head change from lowest to highest, which is safe and reliable to use. It has higher power of self-priming. The maximum suction depth of the well is 30m. It is suitable for water supply from a 4" well to be used for modern domestic applications and industrial applications, and will ensure enough water to supply all user outlets.

AUJETDP系列自动供水系统由离心泵、压力罐、压力开关、喷嘴、射流器组成。其压力从最小到最大所需要的功率变化不大，故操作安全可靠具有较高的自吸能力，最大自吸深度可达30米。适用于城市和工业从4寸井中供水压力的增加从而实现自动供水并将确保所有用户足够的水供应。

WORKING CONDITIONS

- Max Temperature of Fluid up to +40°C
- Max Pressure 10bar
- Max Ambient Temperature up to 40°C

工作条件：

- 最高流体温度为40°C
- 最大可承受的压力10bar
- 最高环境温度40°C

技术参数 TECHNICAL DATA AT 220~240V/50Hz

型号 TYPE	输入功率 Input Power		电流 Current (A)	最大流量 Q.max (l/min)	最高扬程 H.max (m)	最大吸程 Such.max (m)	转速 Speed (r/min)	压力开关 Pressure Switch		连接管径 Pipe Diameter (inch)	包装尺寸 Packing Size (mm)	毛重 GW (kg)	包装数量 Packing QTY. 20'柜(Cont)
	KW	HP						开 ON	关 OFF				
AUJDW-370	0.37	1/2	2.6	20	25	15	2850	1.4 Bar	2.6 Bar	1.25"x1"x1"	435x300x230 Tank410x270x270	20	470
AUJDW-550	0.55	3/4	3.6	25	30	20				1.25"x1"x1"		21.5	470
AUJDW-750	0.75	1	4.8	30	35	25				1.25"x1"x1"		22	470
AUJETDP-370	0.37	1/2	2.6	25	25	15				1.25"x1"x1"	400x300x230 Tank410x270x270	20	470
AUJETDP-550	0.55	3/4	3.6	30	30	20				1.25"x1"x1"		21.5	470
AUJETDP-750	0.75	1	4.8	35	35	25				1.25"x1"x1"		22	470
AUJETDP-1100	1.1	1.5	6.6	40	55	20				1.25"x1"x1"		535x250x300 Tank410x270x270	31
AUJETDP-1500	1.5	2	8.8	45	65	25				1.25"x1"x1"	33		420

Note: 110V/60Hz, 115V/60Hz, 127V/60Hz, 110/220V/60Hz, 380V/50Hz ets. Models are available on request
备注: 可以按要求生产110V/60Hz, 115V/60Hz, 127V/60Hz, 110/220V/60Hz等电压频率